



# AG100-003



## Universal Triple Air Gap for Water Filters with Three 3/8-inch OD Inlet Ports (AG100-003)

### Features:

- Three 3/8-inch OD inlet ports for direct connection to 3/8-inch ID poly tube
- Installs in both 1-1/2-inch and 2-inch standpipes
- Built-in splash guards to assure a completely dry operation
- Standpipes can accommodate up to 3 units at a time
- Legal to install in any state, UPC® Listed, IPC® and NSF® tested

### General Description:

The AG100-003 Universal Triple Air Gap is designed to provide an effective way of connecting water filters to a drain line. The paramount priority of the AG100-003 is to protect the water supply. The AG100-003 easily connects iron filters, reverse osmosis filters, or boilers purge lines to a standpipe through a code-compliant air gap. It also can be used for condensate drainage from air-conditions, or sump pumps.

The AG100-003 air gap features three inlet ports that connect 3/8-inch ID tubing from water filters to the drain line. The unique feature of this air gap is to be able to accommodate 1-1/2-inch and 2-inch stand drainpipes. Also, a unique design of this air gap enables the installation of multiple air gaps into the same drain connection. Up to three AG100-003s can be installed into the same drain line to provide a total of nine simultaneous water discharge connections.

The AG100-003 air gap provides a secure connection between the discharge tubing and a drain line.

### Mechanical Specifications:

- Width: 2-inches
- Height: 6-1/2-inches
- Air gap Size: >1 inch

### Inlet/Outlet Specifications:

- Inlet: 3/8-inch OD
- Outlet: Fits 1-1/2 to 2 inches standpipe drains

### Material

- Body: Polystyrene, Gray

### Approvals

- UPC: Listed
- IPC: Tested by independent lab
- NSF: Tested by independent lab