



AG100-004



Universal Triple Air Gap for Water Filters with Dual 3/8-inch OD ports and Single 1/4-inch OD port (AG100-004)

Features:

- Two 3/8-inch and one 1/4-inch OD inlet ports
- Installs in both 1-1/2-inch and 2-inch standpipes
- Built-in splash guards to assure a completely dry operation
- Standpipes can accommodate up to 3 units at a time
- Legal to install in any state, UPC® Listed, IPC® and NSF® tested

General Description:

The AG100-004 Universal Triple Air Gap is designed to provide an effective way of connecting water filters to a drain line. The paramount priority of the AG100-004 is to protect the water supply. The AG100-004 easily connects iron filters, reverse osmosis filters, or boilers purge lines to a standpipe through a code-compliant air gap. It also can be used for condensate drainage from air-conditions, or sump pumps.

The AG100-004 air gap features three inlet ports that connect two 3/8-inch ID and one 1/4-inch ID tubing from water filters to the drain line. The unique feature of this air gap is to be able to accommodate 1-1/2-inch and 2-inch stand drainpipes. Also, a unique design of this air gap enables the installation of multiple air gaps into the same drain connection. Up to three AG100-004s can be installed into the same drain line to provide a total of nine simultaneous water discharge connections.

The AG100-004 air gap provides a secure connection between the discharge tubing and a drain line.

Mechanical Specifications:

- Width: 2-inches
- Height: 6-1/2-inches
- Air gap Size: >1 inch

Inlet/Outlet Specifications:

- Inlet: Two 3/8-inch OD, One 1/4-inch OD
- Outlet: Fits 1-1/2 to 2 inches standpipe drains

Material

- Body Polystyrene, Gray

Approvals

- UPC Listed
- IPC Tested by independent lab
- NSF Tested by independent lab