

AG170-008



Dual Barb Elbow with 5/8-in OD barb x 1/2-in and 5/8-in OD barb for AG100-001/AG130-001

Features:

- Easy connection to discharge hoses
- Accommodates a 5/8-inch ID slip joint
- Accommodates 1/2-inch or 5/8-inch ID discharge hose.
- Tested for 8 GPM flow rate
- Can be used with steel worm clamps
- Enables users to cut the barb to size
- Does not deteriorate with time

General Description:

The AG170-008 is a right-angle barb elbow connecting a 5/8-inch ID slip joint on one end to a 1/2-inch or 5/8-inch ID hose/tubing on the other. Dual barb different hose sizes are used in water softeners or RO filters. If a 1/2-inch barb is not used, cut it off to access a 5/8-inch barb.

The AG170-008 is made from high-impact polystyrene and is strong enough to secure the hose with stainless steel metal worm clamps. The AG170-008 is ideal for water softeners, RO systems, and other water-processing appliances.

Mechanical Specifications:

- Width (5/8 barb): 2-1/4-inches
- Height (multi barb): 2-1/8-inches

Inlet/Outlet Specifications:

- Inlet (barb): 1/2, 5/8 inch
- Outlet (barb): 5/8 inch

Flow Rate: 8 GPM

Material

- Body: High-impact Polystyrene