



AG200-005



Dual Air Gap for Dishwasher and Reverse Osmosis Filters (with tank) and extra-long thread

Features:

- Can simultaneously drain dishwasher and RO system (with tank)
- Accepts standard 5/8-inch I.D. hose from a dishwasher
- Connects to drain with 7/8-inch I.D. hose
- Provides 1/4-inch push-in connector for RO discharge
- Eliminates gurgling or dripping sounds
- Provides extra-long thread for mounting through a thick counter-top
- UPC® listed, tested for compliance to IPC® and NSF® standards
- Not compatible with RO faucets with air gap

General Description:

A dishwasher air gap is a critical component in maintaining a safe water supply. It prevents contaminants in the sink from flowing into the dishwasher and is required by code in most states.

The AMERIGAP brand dual air gap provides two inlet ports for simultaneous drainage of discharge water from a single dishwasher, and a reverse osmosis filter with tank. The combination of two air gaps in one provides an easy way to connect the RO system into drainage system safely.

This air gap is easy to use and legal to install in any state. The AG200-005 air gap is listed by UPC® and tested for compliance with IPC® and NSF® standards.

Mechanical Specifications:

- Length: 5-1/2 inches
- Width: 1-7/8 inches
- Height above counter: 2-1/2 inches
- Total Height: 7-13/20 in. (7.65 in.)

Accessories (included):

- Cover cap
- Bottom nut
- Mounting washer
- Top housing
- Mounting nut
- Top nut
- Inlet plug

Alternative PN:

- T52 RO KIT, AMERIGAP

Inlet/Outlet Specifications:

- Inlet (dishwasher): 5/8-inch OD
- Inlet (RO): 1/4-inch push-in
- Outlet: 7/8-inch OD

Material

- Body: Polypropylene
- Decorative cap: Chrome plated ABS
- Max. Temperature: 170°F / 76°C

Approvals, Standards and Certifications

- UPC: Listed
- IPC: Tested by independent lab
- NSF: Tested by independent lab
- ASME: A112.1.3