



AG200-008



Triple Air Gap for Double Drawer or Two Separate Dishwashers and a Reverse Osmosis filter with Extra Long Thread

Features:

- Can simultaneously drain a double drawer dishwasher and RO system (with or without tank)
- Accepts standard 5/8-inch I.D. hoses from a double drawer dishwasher or two separate dishwashers
- Connects to drain with 7/8-inch I.D. hose
- Provides 1/4-inch push-in connector for RO discharge
- Eliminates gurgling or dripping sounds
- Provides extra-long thread for mounting through a thick counter-top
- UPC® listed, tested for compliance to IPC® and NSF® standards
- Not compatible with RO faucets with air gap

General Description:

A dishwasher air gap is a critical component in maintaining a safe water supply. It prevents contaminants in the sink from flowing into the dishwasher and is required by code in most states.

The AMERIGAP brand dual air gap provides two inlet ports for simultaneous drainage of discharge water from a double drawer dishwasher or two separate dishwashers, and one inlet port for a reverse osmosis filter. The RO inlet port accommodates both with tank and tankless reverse osmosis filters. A three-in-one air gap provides an easy way to connect the RO system into the drainage.

This air gap is easy to install, easy to use, and easy to maintain.

Mechanical Specifications:

- Length: 5-1/2 inches
- Width: 1-7/8 inches
- Height above counter: 2-1/2 inches
- Total Height: 7.88 inches

Accessories (included):

- Cover cap
- Bottom nut
- Mounting washer
- Top housing
- Mounting nut
- Top nut

Inlet/Outlet Specifications:

- Inlets (dishwasher): 5/8-inch OD
- Inlet (RO): 1/4-inch push-in
- Outlet: 7/8-inch OD

Material

- Body: Polypropylene
- Decorative cap: Chrome plated ABS
- Max. Temperature: 170°F / 76°C

Approvals, Standards and Certifications

- UPC: Listed
- IPC: Tested by independent lab
- NSF: Tested by independent lab
- ASME: A112.1.3