

ET117-001



Multipurpose Air Gap with 3/8-inch Quick Connect for Installation on a 1-1/2-inch Standpipe with ABS Trap Adapters

Features:

- Provides easy connection to 1-1/2-inch standpipe drain
- Splash guard assures completely dry operation
- Quick connect push-in inlet connector
- Recommended usage up to 15 gallons/minute flow rate
- Legal to install in any state, UPC[®] and IPC[®] Listed
- Not compatible with RO faucets with air gap

General Description:

The ET117-001 multipurpose air gap is designed to provide a convenient way to install an air gap into a 1-1/2inch standpipe drain. This air gap can be connected to a water filtration system using flex tubing. The air gap's splash-resistant design protects the air gap's surroundings from water damage. The inlet accommodates flex tubing for leak-proof installation in tight spaces. The right-angle inlet provides a convenient way of connecting discharge water tubing to a drain line.

This air gap is easy to use and legal to install in any state. The ET117 series air gaps are UPC (Uniform Plumbing code) and IPC (International Plumbing Code) listed.

Mechanical Specifications:

- ·····
 - Width: 2 inches
 - Height: 4 inches

Accessories (included):

- 1-1/2-inch ABS hub to male pipe thread trap adapter
- 1-1/2-inch ABS spigot to male pipe thread trap adapter
- 1-1/2-inch ABS slip joint wing nut
- 1-1/2-inch O-ring
- 1-1/2-inch slip joint beveled washer

Alternative PN:

• G-38QCA, DLA-G

Inlet/Outlet Specifications:

- Inlet: 3/8-inch push-in
- Outlet:

Material

Body Glass white polypropylene

1-1/2 inches

Approvals

- UPC
 - Listed Tested by independent lab
 - IPC Tested by independent lab NSF Tested by independent lab

AirGap International a Division of Altinex Inc. 500 Jefferson St. Placentia, CA 92870