

ET117-002



Multipurpose Air Gap with 3/8-inch Quick Connect for Installation on a 1-1/2-inch Standpipe with PVC Trap Adapters

Features:

- Provides easy connection to 1-1/2-inch standpipe drain
- Splash guard assures completely dry operation
- Quick connect push-in inlet connector
- Recommended usage up to 15 gallons/minute flow rate
- Legal to install in any state, UPC® Listed, IPC® and NSF® tested
- Not compatible with RO faucets with air gap

General Description:

The ET117-002 multipurpose air gap is designed to provide a convenient way to install an air gap into 1-1/2-inch standpipe drain. This air gap can be connected to a water filtration system using flex tubing. The air gap's splash-resistant design protects the air gap's surroundings from water damage. The inlet accommodates flex tubing for leak-proof installation in tight spaces. The right-angle inlet provides a convenient way of connecting discharge water tubing to a drain line.

This air gap is easy to use and legal to install in any state. The ET117 series air gaps are listed by UPC (Uniform Plumbing code) and tested for compliance with IPC (International Plumbing Code) and NSF standards.

Mechanical Specifications:

Width: 2 inchesHeight: 4 inches

Accessories (included):

- 1-1/2-inch Schedule-40 PVC hub to male pipe thread trap adapter
- 1-1/2-inch Schedule-40 PVC spigot to male pipe thread trap adapter
- 1-1/2-inch slip joint wing nut
- 1-1/2-inch O-ring
- 1-1/2-inch PVC slip joint beveled washer

Alternative PN:

G-38QCP, DLA-G

Inlet/Outlet Specifications:

•	Inlet:	3/8-inch push-in
•	Outlet:	1-1/2 inches

Material

•	Body	Glass white polypropylene
	200,	Grass trinte porypropyrene

Approvals

•	UPC	Listed
•	IPC	Tested by independent lab
•	NSF	Tested by independent lab