

## ET117-006



### Water Softener Air Gap with 5/8-inch JACO Compression for Installation on a 1-1/2-inch Standpipe with PVC Trap Adapters

#### Features:

- Provides easy connection to 1-1/2-inch standpipe drain
- Splash guard assures completely dry operation
- Quick connect push-in inlet connector
- Recommended usage up to 15 gallons/minute flow rate
- Legal to install in any state, UPC® Listed, IPC® and NSF® tested

#### General Description:

The ET117-006 water softener air gap is designed to provide a convenient way to install an air gap into a 1-1/2-inch standpipe drain. The air gap's splash-resistant design protects the air gap's surroundings from water damage. The inlet accommodates flex tubing for leak-proof installation in tight spaces. The right-angle inlet provides a convenient way of connecting discharge water tubing to a drain line.

This air gap is easy to use and legal to install in any state. The ET117 series air gaps are listed by UPC (Uniform Plumbing code) and tested for compliance with IPC (International Plumbing Code) and NSF standards.

#### Mechanical Specifications:

- Width: 3 inches
- Height: 4 inches

#### Accessories (included):

- 1-1/2-inch Schedule-40 PVC hub to male pipe thread trap adapter
- 1-1/2-inch Schedule-40 PVC spigot to male pipe thread trap adapter
- 1-1/2-inch slip joint wing nut
- 1-1/2-inch O-ring
- 1-1/2-inch PVC slip joint beveled washer

#### Alternative PN:

- G-58JA, DLA-G

#### Inlet/Outlet Specifications:

- Inlet: 5/8-inch
- Outlet: 1-1/2 inches

#### Material

- Body: Glass white polypropylene

#### Approvals

- UPC: Listed
- IPC: Tested by independent lab
- NSF: Tested by independent lab