

## ET117-006



## Water Filter/Softener Air Gap with 5/8-inch JACKO Compression for Installation on a 1-1/2-inch Standpipe with PVC Trap Adapters

### Features:

- Provides easy connection to 1-1/2-inch standpipe drain
- Splash guard assures completely dry operation
- Quick connect push-in inlet connector
- Recommended usage up to 15 gallons/minute flow rate
- Legal to install in any state, UPC® Listed, IPC® and NSF® tested

### General Description:

The ET117-006 universal water softener or water filter air gap is designed to provide a convenient way to install an air gap into 1-1/2-inch standpipe drain. This air gap can be connected to a water filtration system using flex tubing. The unique design provides a completely protected air gap without any possibility of water splashing out. The inlet accommodates flex tubing for a leak-proof installation in tight spaces. The right-angle inlet provides a convenient way of connecting discharge water tubing to a drain line through air gap.

The ET117-006 air gap is easy to use and legal to install in any state. The ET117-006 air gap is listed by UPC (Uniform Plumbing code) and tested for compliance with IPC (International Plumbing Code) and NSF standards.

### Mechanical Specifications:

- Width: 3 inches
- Height: 4 inches

### Accessories (included):

- 1-1/2-inch Schedule-40 PVC hub to male pipe thread trap adapter
- 1-1/2-inch Schedule-40 PVC spigot to male pipe thread trap adapter
- 1-1/2-inch slip joint wing nut
- 1-1/2-inch O-ring
- 1-1/2-inch PVC slip joint beveled washer

### Alternative PN:

- G-58JA, DLA-G

### Inlet/Outlet Specifications:

- Inlet: 5/8-inch
- Outlet: 1-1/2 inches

### Material

- Body: Glass white polypropylene

### Approvals

- UPC: Listed
- IPC: Tested by independent lab
- NSF: Tested by independent lab