



ET117-009

RO Water Filter Air Gap with 1/4-inch Quick Connect for Installation on a 1-1/2-inch Standpipe with ABS Trap Adapters



Features:

- Provides easy connection to 1-1/2-inch standpipe drain
- Splash guard assures completely dry operation
- Recommended flow rate up to 7 gallons/minute
- Quick connect push-in inlet connector
- Legal to install in any state, UPC® Listed, IPC® and NSF® tested
- Not compatible with RO faucets with air gap

General Description:

The ET117-009 RO water filter air gap is designed to provide a convenient way to install an air gap into a 1-1/2-inch standpipe drain. This air gap can be connected to a water filtration system using flex tubing. The air gap's splash-resistant design protects the air gap's surroundings from water damage. The inlet accommodates flex tubing for leak-proof installation in tight spaces. The right-angle inlet provides a convenient way of connecting discharge water tubing to a drain line.

This air gap is easy to use and legal to install in any state. The ET117 series air gaps are listed by UPC (Uniform Plumbing code) and tested for compliance with IPC (International Plumbing Code) and NSF standards.

Mechanical Specifications:

- Width: 2 inches
- Height: 4 inches

Accessories (included):

- 1-1/2-inch ABS hub to male pipe thread trap adapter
- 1-1/2-inch ABS spigot to male pipe thread trap adapter
- 1-1/2-inch ABS slip joint wing nut
- 1-1/2-inch O-ring
- 1-1/2-inch slip joint beveled washer
- Drip noise prevention membrane

Inlet/Outlet Specifications:

- Inlet: 1/4-inch push-in
- Outlet: 1-1/2 inches

Material

- Body: Glass white polypropylene

Approvals

- UPC: Listed
- IPC: Tested by independent lab
- NSF: Tested by independent lab