



Dual Air Gap for Double Drawer Dishwasher

Features:

- Can simultaneously drain both dishwasher drawers
- Accepts standard 5/8-inch I.D. hoses from a dual dishwasher •
- Connects to drain with 7/8-inch I.D. hose •
- Easy to install in tight installations •
- Colored cap available separately ٠
- UPC® listed, tested for compliance to IPC® and NSF® standards •
- Not compatible with RO faucets with air gap

General Description:

A dishwasher air gap is a critical component in maintaining a safe water supply. It prevents contaminants in the sink from flowing into the dishwasher and is required by code in most states.

The ET200-002 dual dishwasher air gap provides many advantages over other air gaps available on the market and also ensures safety and peace of mind that your water supply is clean.

A common misconception is that a "high loop" (routing a drain line under the counter, for instance) and a wye connection will provide the same function as an air gap; this is not true, because the continuous connection between dishwasher and drain line still will allow back-flow through siphoning.

This air gap is easy to use and legal to install in any state. The ET200-002 air gap is listed by UPC and tested for compliance with IPC and NSF standards.

Mechanical Specifications:

- Length:
 - 3-3/4 inches Width: 2-1/4 inches
- Height (with cap): 3 inches
- Total Height: 9 inches •

Accessories (included):

- Inner cap •
- **Compression Top Nut**
- Deck Mount Middle Nut Undercounter Bottom Nut •
- Chrome Cover Cap •

Alternative PN:

TAG-58BI, DLA-TAG

- Deck Gasket
- **Inner Cap Custom** •
- O-Ring
- 1/2-inch MIPT x 5/8-inch barb adapter

Inlet/Outlet Specifications:

- 5/8-inch OD Inlet:
- Outlet: 7/8-inch OD

Material

- Polypropylene
- Decorative cap

Body

Approvals

- UPC
- IPC NSF

Chrome plated ABS

- Listed
- Tested by independent lab
- Tested by independent lab

AirGap International a Division of Altinex Inc. 500 Jefferson St. Placentia, CA 92870