



AG150-001

In-line Air Gap



Features:

- Provides an in-line air gap
- Unit can be tilted up to 45° angle if needed, (window opening on top side)
- Easy vertical wall mounting with included “Jiffy Clip”
- Incorporates a rotatable splash guard/splatter shield
- Recommended usage up to 7 gallons/minute (26.5 liters/minute)

General Description:

The AG150 series inline water softener or water filter air gaps are designed to provide a convenient way to install air gap which may be tilted up to 45 degrees. This air gap can be connected using flex tubing or a rigid PVC pipe. The unique design provides a completely protected airgap without any possibility of water splashing out. The rotating protection sleeve assures long and trouble-free operation and impedes insects’ ingress. The inlet can accommodate 1/4-inch FIP adapters or 1/2-inch threaded PVC adapters, the outlet can accommodate 3/4-inch threaded PVC adapters or 5/8 OD tubing.

It is easy to use and legal to install in any state. The AG150 series air gap is UPC® and IPC® listed.

Mechanical Specifications:

- Width: 1-1/4 inches
- Height: 8 inches

Inlet/Outlet Specifications:

- Inlet: 1/4-inch FIP or 1/2-inch thread
- Outlet: 5/8-inch OD

Accessories:

- Splash guard
- 5/8-inch seal washers
- Injector washer
- Jiffy Clip

Material

- Body BLACK ABS / 20% GLASS FILLED

Approvals

- UPC Listed
- IPC Tested by independent lab

Alternative PN:

- 211211