



## AG200-X05



### Dual Air Gap for Dishwasher and Reverse Osmosis Filters (with tank) and extra-long thread Features:

- Offers a variety of decorative cap finishes designed to complement your kitchen sink faucet (**AG200-005 to AG200-805**).
- Can simultaneously drain dishwasher and RO system (with tank)
- Accepts standard 5/8-inch I.D. hose from a dishwasher
- Connects to drain with 7/8-inch I.D. hose
- Provides 1/4-inch push-in connector for RO discharge
- Eliminates gurgling or dripping sounds
- Provides extra-long thread for mounting through a thick counter-top
- UPC® and IPC® listed
- Not compatible with RO faucets with air gap

#### General Description:

A dishwasher air gap is a critical component in maintaining a safe water supply. It prevents contaminants in the sink from flowing into the dishwasher and is required by code in most states.

The AMERIGAP brand dual air gap provides two inlet ports for simultaneous drainage of discharge water from a single dishwasher, and a reverse osmosis filter with tank. The combination of two air gaps in one provides an easy way to connect the RO system into drainage system safely.

This air gap is easy to use and legal to install in any state. The AG200-X05 air gap is UPC® and IPC® listed.

#### Mechanical Specifications:

- Length: 5-1/2 inches
- Width: 1-7/8 inches
- Height above counter: 2-1/2 inches
- Total Height: 7-13/20 in. (7.65 in.)

#### Inlet/Outlet Specifications:

- Inlet (dishwasher): 5/8-inch OD
- Inlet (RO): 1/4-inch push-in
- Outlet: 7/8-inch OD

#### Material

#### Accessories (included):

- Cover cap
- Bottom nut
- Mounting washer
- Top housing
- Mounting nut
- Top nut
- Inlet plug

- Body Polypropylene
- Decorative cap Chrome plated ABS (**AG200-005**)  
Brass (**AG200-105 to -805**)
- Max. Temperature 170°F / 76°C

#### Approvals, Standards and Certifications

#### Alternative PN:

- T52 RO KIT, AMERIGAP

- UPC Listed
- IPC Tested by independent lab
- ASME A112.1.3