



## ET115-001



### Water Filter/Softener Air Gap With 1/2-inch Female Thread Inlet for Use With 1-1/2-inch Standpipe

#### Features:

- Provides easy connection to 1-1/2-inch standpipe
- Splash guard assures completely dry operation
- Can be pressure fit or glued to a standpipe
- Minimum flow rate at 0.5 GPM and maximum flow rate at 7 GPM
- Legal to install in any state, UPC® and IPC® listed

#### General Description:

The ET115 series universal water softener or water filter air gaps are designed to provide a convenient way to install an air gap into 1-1/2-inch standpipe drain. This air gap can be connected using a rigid PVC pipes or flex tubing with adapters. The unique design provides a completely protected air gap without any possibility of water splashing out. The inlet accommodates 1/2-inch threaded PVC pipes or adapters.

It is easy to use and legal to install in any state. The ET115 series air gap is UPC and IPC listed.

#### Mechanical Specifications:

- Width: 2-3/8 inches
- Height: 4-1/4 inches

#### Alternative PN:

- G-150, DLA-G15

#### Temperature Rating:

- Operating Temp. 70°C (158°F)
- Peak Temp. 80°C (176°F)

#### Inlet/Outlet Specifications:

- Inlet: 1/2-inch NPT Schedule 40
- Outlet: 1-1/2 inches ID

#### Material

- Body Delta Polymer

#### Approvals

- UPC Listed
- IPC Tested by independent lab