



ET115-002



Water Filter/Softener Air Gap With 3/4-inch Female Thread Inlet for Use With 1-1/2-inch Standpipe

Features:

- Provides easy connection to 1-1/2-inch standpipe
- Splash guard assures complete dry operation
- Can be pressure fit or glued to a standpipe
- Minimum flow rate at 0.5 GPM and maximum flow rate at 9 GPM
- Legal to install in any state UPC® and IPC® Listed

General Description:

The ET115 series universal water softener or water filter air gaps are designed to provide a convenient way to install an air gap into 1-1/2-inch standpipe drain. This air gap can be connected using a rigid PVC pipes or flex tubing with adapters. The unique design provides a completely protected air gap without any possibility of water splashing out. The inlet accommodates 3/4-inch threaded PVC pipes or adapters.

It is easy to use and legal to install in any state. The ET115 series air gap is listed by UPC and IPC.

Mechanical Specifications:

- Width: 2-3/8 inches
- Height: 4-1/4 inches

Alternative PN:

- G-175, DLA-G15

Temperature Rating:

- Operating Temp. 70°C (158°F)
- Peak Temp. 80°C (176°F)

Inlet/Outlet Specifications:

- Inlet: 3/4-inch NPT Schedule 40
- Outlet: 1-1/2 inches ID

Material

- Body Delta Polymer

Approvals

- UPC Listed
- IPC Tested by independent lab