

ET117-002



Features:

- Provides easy connection to 1-1/2-inch standpipe drain
- Splash guard assures completely dry operation
- Quick connect push-in inlet connector
- Recommended usage up to 15 gallons/minute flow rate
- Legal to install in any state, UPC® and IPC® Listed
- Not compatible with RO faucets with air gap

General Description:

The ET117-002 multipurpose air gap is designed to provide a convenient way to install an air gap into 1-1/2-inch standpipe drain. This air gap can be connected to a water filtration system using flex tubing. The air gap's splash-resistant design protects the air gap's surroundings from water damage. The inlet accommodates flex tubing for leak-proof installation in tight spaces. The right-angle inlet provides a convenient way of connecting discharge water tubing to a drain line.

This air gap is easy to use and legal to install in any state. The ET117 series air gaps are UPC (Uniform Plumbing code) and IPC (International Plumbing Code) listed.

Mechanical Specifications:

- Width: 2 inches
- Height: 4 inches

Inlet/Outlet Specifications:

- Inlet: 3/8-inch push-in
- Outlet: 1-1/2 inches

Accessories (included):

- 1-1/2-inch Schedule-40 PVC hub to male pipe thread trap adapter
- 1-1/2-inch Schedule-40 PVC spigot to male pipe thread trap adapter
- 1-1/2-inch slip joint wing nut
- 1-1/2-inch O-ring
- 1-1/2-inch PVC slip joint beveled washer

Material

- Body: Glass white polypropylene

Approvals

- UPC: Listed
- IPC: Tested by independent lab

Alternative PN:

- G-38QCP, DLA-G