



ET117-005



Water Softener Air Gap with 5/8-inch JACO Compression for Installation on a 1-1/2-inch Standpipe with ABS Trap Adapters

Features:

- Provides easy connection to 1-1/2-inch standpipe drain
- Splash guard assures completely dry operation
- Quick connect push-in inlet connector
- Recommended usage up to 15 gallons/minute flow rate
- Legal to install in any state, UPC® and IPC® listed

General Description:

The ET117-005 water softener air gap is designed to provide a convenient way to install an air gap into a 1-1/2-inch standpipe drain. This air gap can be connected to a water filtration system using flex tubing. The air gap's splash-resistant design protects the air gap's surroundings from water damage. The inlet accommodates flex tubing for leak-proof installation in tight spaces. The right-angle inlet provides a convenient way of connecting discharge water tubing to a drain line.

This air gap is easy to use and legal to install in any state. The ET117 series air gaps are UPC (Uniform Plumbing code) and IPC (International Plumbing Code) listed.

Mechanical Specifications:

- Width: 3 inches
- Height: 4 inches

Inlet/Outlet Specifications:

- Inlet: 5/8-inch
- Outlet: 1-1/2 inches OD

Accessories (included):

- 1-1/2-inch ABS hub to male pipe thread trap adapter
- 1-1/2-inch ABS spigot to male pipe thread trap adapter
- 1-1/2-inch ABS slip joint wing nut
- 1-1/2-inch O-ring
- 1-1/2-inch slip joint beveled washer

Material

- Body: Glass white polypropylene

Approvals

- UPC: Listed
- IPC: Tested by independent lab

Alternative PN:

- G-58JA, DLA-G