

ET117-008



Water Softener Air Gap with 1/2-inch Barb Connector for Installation on a 1-1/2-inch Standpipe with PVC Trap Adapters

Features:

- Provides easy connection to 1-1/2-inch standpipe drain
- Splash guard assures completely dry operation
- Quick connect push-in inlet connector
- Recommended usage up to 15 gallons/minute flow rate
- Legal to install in any state, UPC® and IPC® listed

General Description:

The ET117-008 water softener air gap is designed to provide a convenient way to install an air gap into a 1-1/2-inch standpipe drain. The air gap's splash-resistant design protects the air gap's surroundings from water damage. The inlet accommodates flex tubing for leak-proof installation in tight spaces. The right-angle inlet provides a convenient way of connecting discharge water tubing to a drain line.

This air gap is easy to use and legal to install in any state. The ET117 series air gaps are listed by UPC (Uniform Plumbing code) and IPC (International Plumbing Code) listed.

Mechanical Specifications:

Width: 3 inchesHeight: 4 inches

Accessories (included):

- 1-1/2-inch Schedule-40 PVC hub to male pipe thread trap adapter
- 1-1/2-inch Schedule-40 PVC spigot to male pipe thread trap adapter
- 1-1/2-inch slip joint wing nut
- 1-1/2-inch O-ring
- 1-1/2-inch PVC slip joint beveled washer

Alternative PN:

G-50BP, DLA-G

Inlet/Outlet Specifications:

•	Inlet:	1/2-inch barb
•	Outlet:	1-1/2-inch OD

Material

•	Body	Glass white polypropylene
---	------	---------------------------

Approvals

•	UPC	Listed

• IPC Tested by independent lab