



ET120-001



Water Softener Filter Air / Condensate Air Gap for 2-inches Standpipe and 1- inch Threaded Inlet

Features:

- 1-inch threaded inlet for use with MIPT Schedule-40 nipples and adapters
- Installs onto 2-inches ABS or PVC Schedule-40 standpipes
- Made from white ABS resin to ASTM specifications
- Solid connection ensures a professional installation
- Prevents splash or spray
- Minimum flow rate at 6 GPM and maximum flow rate at 22 GPM
- UPC® and IPC® listed, ASME A112.1.3 compliant

General Description:

The ET120-001 Universal Air Gap is designed for commercial water treatment equipment and condensate lines that require an air gap discharge to the drain. This air gap drain line adapter is perfect for applications where rigid Schedule-40 pipe must be plumbed to an approved air gap device. The ET120-001 provides a convenient, ready-made, true air gap for all Schedule-40 DWV standpipes.

This air gap is easy to use and legal to install in any state. The ET120 air gap is UPC and IPC listed.

Mechanical Specifications:

- Width: 2-3/4 inches
- Height: 4-1/2 inches

Alternative PN:

- ET120-001, G-200, DLA-G20

Temperature Rating:

- Operating Temp. 70°C (158°F)
- Peak Temp. 80°C (176°F)

Inlet/Outlet Specifications:

- Inlet: 1-inch NPT Schedule 40
- Outlet: 2 inches ID

Material

- Body Glass white polypropylene

Approvals

- UPC Listed
- IPC Tested by independent lab